



The Technical Specification Sheet For Indoor Products (Marble Tiles Bzaluon)

Item :	Description & Specifications		
Product uses:	A thickness one single layer tile with polished , smooth texture face such as marble, very hard and resist to bending ,abrasion and water absorption with a high degree Pack. It is produced by more than 50 colors and also produces a button with its own code from the same tile cod. it used in all types of cladding floors inside the building, including apartments, rooms and halls and roof villas, offices and administrative buildings and schools (classes, methods and offices), restaurants of all kinds of hotels and squares.		
Available sizes:	30×30×1.8 cm , 40×40×2 cm and the size 50×50×2.5 cm and with the possibility of the implementation of special orders increase the thickness of the tiles as requested by the client.		
	30 × 30 × 1.8 cm	40 × 40 × 2 cm	50 × 50 × 2.5cm
Length :	300 mm	400 mm	500 mm
Width :	300 mm	400 mm	500 mm
Thickness	18 mm	20 mm	25 mm
Units per 1 M.sq:	11.11 Tile	6.25 Tile	4 Tiles
Unit weight :	3.42 Kg	6.88 Kg	13.25 Kg
M.sq weight :	38.0 Kg	43.0 Kg	53 Kg
Density :	2.11g/cm ³	2.11g/cm ³	2.11g/cm ³
Technical tests:	Standard by Bs 4131 && [Es : 269-2]		
1- Absorption:	0.8 %		
2-Abrasion :	0.6 mm		
3-Bending :	75.kg / cm ²		
The mixture :	The product consisting of marbles shapes , marble powder , white cement, and oxides (iron) upon requested colored .		

